

06/14/00
 0613 U.S. PTO

06-15-00

A

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/2000. OMB 0651-0032
 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL <small>*Only for new nonprovisional applications under 37 C.F.R. § 1.53(b)</small>	Attorney Docket No.	CON1246-076
	First Inventor or Application Identifier	Pirasteh et al.
	Title	METHOD AND SYSTEM FOR PROCESSING TELEPHONE CALLS BY IVR
	Express Mail Label No.	EL622261208US

APPLICATION ELEMENTS <small>See MPEP chapter 600 concerning utility patent application contents.</small>	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing)	5. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification [Total Pages 23] (preferred arrangement set forth below) - Descriptive title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure	6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 3]	ACCOMPANYING APPLICATION PARTS 7. <input type="checkbox"/> Assignment Papers (cover sheet & document(s)) 8. <input type="checkbox"/> 37 C.F.R. §3.73(b) Statement (when there is an assignee) <input type="checkbox"/> Power of Attorney 9. <input type="checkbox"/> English Translation Document (if applicable) 10. <input checked="" type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input checked="" type="checkbox"/> Copies of IDS Citations 11. <input type="checkbox"/> Preliminary Amendment 12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 13. <input type="checkbox"/> Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application, (PTO/SB/09-12) <input type="checkbox"/> Status still proper and desired 14. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 15. <input type="checkbox"/> Other:
4. Oath or Declaration [Total Pages 3] a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 16 completed) <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	

* NOTE FOR ITEMS 12 & 13 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 CFR, § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28)

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____ Group/Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label or ☒ Correspondence address below

Insert Customer No. or Attach bar code label here):

Name	JEFFREY S. STANDLEY				
Address	Standley & Gilcrest LLP 495 Metro Place South, Suite 210				
City	Dublin,	State	Ohio	Zip Code	43017
Country	USA	Telephone	614-792-5555	Fax	614-792-5536

Name (Print/type)	JEFFREY S. STANDLEY	Registration No. (Attorney/Agent)	34,021
Signature		Date	June 14, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

+

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR

METHOD AND SYSTEM FOR PROCESSING
TELEPHONE CALLS BY IVR

Inventors: Hassan Pirasteh
John Garrow
Shelly Grossmith
Khadim Hussain

Assignee: Convergys CMG Utah Inc.
South Jordan, Utah

Attorneys: Standley & Gilcrest LLP
Attn.: Jeffrey S. Standley
495 Metro Place South
Suite 210
Dublin, Ohio 43017-5315
Telephone: (614) 792-5555
Fax: (614) 792-5536

METHOD AND SYSTEM FOR PROCESSING TELEPHONE CALLS BY IVR

Inventors: Hassan Pirasteh, John Garrow,
Shelly Grossmith, Khadim Hussain

BACKGROUND AND SUMMARY OF THE INVENTION

The present invention relates generally to voice response systems. Specifically, this invention relates to an interactive voice response client using script engines to control various voice processing systems.

The development of interactive voice response systems has led to the creation of systems capable of interacting with parties to solicit information in an automated process. Traditionally, business logic for such applications was run on a mainframe. An IVR client would typically "screen-scrape" through the mainframe in order to interface with the agent. Every logic line therefore had to be written on both the mainframe and the IVR client, effectively requiring duplicate coding. The client would need to login to the mainframe, enter data in the mainframe screen and submit the data, monitor the response from the mainframe, and then interpret the data or response received.

It is therefore an object of the present invention to develop an IVR client system wherein logic coding on a main server may be used without the need for analogous logic coding on the client itself.

The present invention comprises a method for processing telephone calls using IVR. The method first involves automatically answering an incoming call. The call is then redirected to an appropriate IVR Engine. A signal is then sent from the IVR Engine to a Script Engine, whereby the Script Engine may run an appropriate script and send an instruction back to the IVR Engine. The IVR Engine then passes the instruction on to the caller. The IVR Engine collects any information provided by

the individual in response to the instruction. If further data collection is needed, the information gathering process may repeat itself until all data is collected from the caller. Once all the data is gathered and, if necessary, processed by the Script Engine, an appropriate message is sent to the individual. The call is then
5 terminated, either automatically or by the individual.

The present invention also includes a system for processing such a telephone call using IVR. The system includes a switch adapted to automatically answer and redirect an incoming call. An IVR Engine then receives the redirected call, and is adapted to send information to and receive information from the caller. The system
10 also includes a Main Script Engine that is adapted to receive an instruction from said IVR Engine, execute an appropriate script, and return an instruction to the IVR Engine. The IVR Engine then uses this instruction to guide the interaction with the individual. The system may also include a data storage device for housing the information received from the caller.

15 In addition to the novel features and advantages mentioned above, other objects and advantages of the present invention will be readily apparent from the following descriptions of the drawings and preferred embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Figure 1 is a schematic diagram of a preferred IVR system in accordance with the present invention.

Figure 2 is another schematic diagram of a preferred IVR system in accordance with the present invention.

Figure 3 is a schematic diagram of the preferred API functions in accordance with the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT(S)

5 The present invention is directed to a system for interfacing with a customer and collecting customer data. Figure 1 shows a diagram of a preferred IVR system **100** of the present invention. A customer or caller **102** dials a designated phone number and is connected to a main switch **104**. The switch then sends a message pertaining to the call to the CTI (Computer Telephony Integration) System **106**. The
10 CTI in turn sends a DNIS or other appropriate message or signal to the IVR Engine **108**. The IVR Engine then preferably sends data back and forth with the caller. The IVR Engine also preferably sends a signal to the main system **110** to run the appropriate script. The main system **110** then sends an instruction to the IVR Engine **108** which is passed on to the caller **102**. The response from the caller **102**
15 to the IVR **108** is then passed on to the Main System **110**. This process repeats itself until all data is gathered or the call is terminated.

Figure 2 shows another view of a preferred system of the present invention. The IVR component architecture preferably contains five basic elements: the IVR Engine **122**, the DIP **124**, the Message Translator **132**, the Main Script Engine
20 Simulator, and the IVR administration tools.

The IVR Engine **122**, an IVR application program residing on IVR machines, preferably executes IVR functionality (i.e., plays voice files and captures digits entered from telephone keypads) as directed by the DIP **124**. The purpose of the IVR application is to provide a main system **126** access to functions unique to IVR,

such as transfer of incoming calls. Execution of business logic will often be a function of such applications. The IVR engine may be derived from any appropriate engine or commercial application, such as Lucent Conversant IVR. A preferred embodiment runs on a UNIX machine connected to an Oracle database for data storage and retrieval, although any appropriate operating system or database may be used. Database scripting may utilize an appropriate commercial package, such as Lucent Script Builder, alleviating the need to generate completely original script. The IVR engine may also incorporate any appropriate voice generation/recognition software, such as Voice@Work. If an Internet or other browser-based client is desired, voice XML or other web-friendly software may be used to interface with a customer.

This IVR Engine preferably answers an incoming call and sends a message to transfer control to the DIP **124**. Upon the receipt of a reply from the DIP, the IVR application may take whatever action is designated and send action complete messages back to the DIP with any collected data. Each new call preferably initiates a stream of messages that are processed back and forth between the IVR Engine and the DIP until the DIP sends the end call or transfer call message. If a caller hangs up before the IVR Engine receives an end call or transfer call message, the engine will preferably send a hang-up message to the DIP.

The DIP **124** is preferably the component on the IVR machine that connects the IVR Engine to the main system. It preferably relays messages between the appropriate Main Script Engine **128**, **130** and the IVR Engine **122**. The communication between the DIP and the Script engine preferably utilizes TCP-IP sockets. The DIP process may usually be started in an 'inittab' on the IVR machine

and may be available to all projects on the main system. Once the IVR Engine receives a call, it preferably calls the DIP with client information. The DIP 124 preferably uses project configuration information to establish a connection to the socket on the appropriate Main Script Engine 128, 130. The DIP relays messages
5 for the call flow from the Main Script Engine to the IVR Engine and any responses back to the Main Script Engine. There may also be messages originating on the IVR Engine 122 like alarms, which are transmitted to the appropriate Main Script Engine. The connection is preferably terminated either by a 'disconnect' or a 'transfer' message from the Main Script Engine call flow or a 'hang-up' message from the IVR
10 Script Engine. The DIP may not store any business knowledge or script 'context' but preferably ensures that each instance of the IVR Engine connects to the corresponding Main Script Engine. It is preferably also able to handle unexpected conditions and re-start itself upon encountering otherwise unrecoverable problems.

The main system may be any appropriate system for warehousing data,
15 applying business rules and logic, and returning data and analysis, such as an SAP system. The SAP or other server, in combination with the Main Script Engine, preferably houses the backend business rules and models and runs all common and/or predetermined APIs. The IVR client then preferably runs the appropriate script. There is then no need to create new logic for the IVR client, as the logic is
20 simply copied from and run on the Main Script Engine.

For example, the Main Script Engine may tell the IVR to capture nine digits for a social security number. The Main Script Engine preferably makes the request in voice form, using the same backend logic. The IVR client then captures the information and sends it to the Main Script Engine, which then validates the data.

This system does away with the need for the IVR client to do such data validation, etc. A pipeline, or socket interface, may be setup between the IVR unit box and the Main system or SAP server. Standard API dialog with predetermined parameters are then preferably written and implemented to interface with the backend business logic on the Main System through the Main Script Engine.

Required maintenance may then be limited primarily to the Main Script Engine. The time needed to develop the IVR client may also be about 10% of the time needed previously, as now the majority of the backend logic is stored and executed exclusively on the main system, not on the client itself. The Main system simply runs the presentation on the IVR client.

The Message Translator component preferably resides on the main system, interpreting incoming messages and translating outgoing messages. It preferably receives instructions from the Main Script Engine, formats the information and sends them on to the IVR DIP. Any response received from the DIP may then be parsed and forwarded to the Main Script Engine. The Message Translator preferably uses TCP-IP sockets to communicate with the IVR DIP.

The Main Script Engine Simulator ("MSES") **134** is a preferred component designed to simulate the Main Script Engine for testing the IVR Engine and the DIP. It may be used as a model to eventually interface the Main Script Engine with the IVR components. It preferably also uses TCP-IP sockets to communicate with the DIP.

The MSES program may handle simple scripts with sufficient capability to test all features supported by the IVR Engine. Once a call comes through and a connection is established to the MSES, it preferably initiates messages to the IVR

DIP through the Message Translator based on a stored script. For the initial phase, it may maintain a sequential script without branching. The call may then be terminated by an appropriate message, such as 'disconnect' or 'transfer', based on the call flow or a 'hang-up' message from the IVR. Multiple instances of the MSES
5 program are preferably able to run asynchronously and interface with an IVR instance. It may also enable the user to inspect the flow of messages to and from the program.

Various administration tasks may also need to be completed with the addition of each new IVR application. Application-specific speech and configuration
10 files/tables are preferably setup for usage by the appropriate IVR components. Support may then be provided for recording script phrases and for administrative message coding. It should also be possible to retrieve customer recorded messages for transcription. Integrity of speech phrases and files across components may be ensured. IVR may utilize such information as incoming VDN,
15 client name, and speech file to execute the appropriate application.

The system preferably includes a configuration file that maps the project id for the incoming Vector Directory Number (VDN) in the IVR Engine. It may also provide the IVR DIP with the location of the Script Engine for all supported projects. This will ensure execution of the appropriate script and successful communication between
20 the IVR Engine and the Main Script Engine. Optionally, the configuration file may maintain version information that is used by the IVR DIP to ensure that the correct version of the script is being executed.

The configuration file preferably stores talkfile numbers associated with the project script and for voice coding, if applicable. In the case of a problem connecting

to the Main Script Engine or an error condition, the IVR Engine may be provided with a default action to either disconnect the caller or transfer the call to an agent at the default transfer number. There may be a phrase associated with this action that is spoken to the caller before it is performed. Finally, the IVR DIP preferably uses the heartbeat interval field in the configuration file to send a heartbeat signal to the main system at that fixed interval and receive a response to ensure a reliable connection and recovery. A sample project entry in the configuration file may look as follows:

```
{  
  VDN=12345  
  PROJECT_ID=MAIN_PROJECT  
  HOST_NAME=maindom  
  VERSION=1.2.3  
  PHRASE_TALKFILE = 123  
  VC_TALKFILE=234  
  DEFAULT_ACTION=TRANSFER  
  DEFAULT_PHRASE=Please hold while you are transferred to a rep.  
  DEFAULT_TRF_NUM=54321  
  HEARTBEAT=10  
}
```

In this example, VDN refers to the incoming Vector Directory Number, PROJECT_ID holds project name information, HOST_NAME holds the TCP/IP host name, VERSION refers to the Main Script version, PHRASE_TALKFILE refers to the IVR Engine recorded speech file, VC_TALKFILE refers to the IVR Engine message coding speech file, DEFAULT_ACTION refers to the IVR Engine default action when instruction cannot be received from the main system, DEFAULT_PHRASE refers to the speech the IVR Engine plays for a default action, DEFAULT_TRF_NUM refers to the number to which the IVR Engine transfers callers for a default transfer, and HEARTBEAT refers to the time interval for sending and receiving heartbeats.

As shown in Figure 3, the system also includes an IVR Applications Program Interface (API) **140**. Several IVR functions may be included in the IVR API. Such functions preferably include, but are not limited to, announcing **142** or speaking a message to the caller; disconnecting **144** or placing the telephone on the hook; 5 collecting **146** or accepting a response from the caller; transferring **148** the caller to another number (such as a customer service representative); recording a caller's speech, coding the message **150**, and storing the message in the main system; speech recognition **152** (such as whole/flex word or text-to-speech); executing events for unexpected hang-ups **154**; and activating alarms **156** for identification of application failure points. Other functions may include temporary IVR transaction 10 suspension, call bridging, terminating one application and starting another without hanging up a call, auto-faxing, and mutli-lingual capability.

Several messages may be sent from the Main Script Engine. Preferred messages include, but are not limited to, Announce, Collect, Transfer Call, Message 15 Coding, Disconnect, and Error Condition.

The main purpose of the Announce function **142** is preferably the playing of messages to provide information to a caller. The message type is preferably specified as phrase, text, or field. The system may speak or play multiple phrases, field values, and/or lines of text. Although phrases are spoken as recorded and text 20 is spoken as it appears in the text string, it is preferably possible to specify the format for the system to use when speaking a field value. The field format preferably determines the speech inflection and the interpretation of data, such as numbers used in money, dates, and times. Upon completion of an Announce function, the IVR preferably sends a message back to the Main Script Engine.

The main purpose of the Collect function **146** is preferably to obtain and pass information input from the caller to the Main Script Engine. It preferably collects caller input through the telephone keypad (touchtone) and/or speech recognition. The function may allow the specification of the caller input parameters and the
5 recognition type for one of the optional speech recognition features. A preferred speech recognition module, such as WholeWord, preferably accepts spoken numbers, 0-9, and the words "yes" and "no".

Caller input parameters are preferably used to guide a caller to enter required data. A caller input field is preferably used to capture the data. Maximum digits,
10 initial timeout and inter-digit timeout parameters are preferably determined from initial configuration, but may optionally be set in the message from the Main Script Engine. The Collect message may include phrase tags that play suitable messages to the caller prior to the actual Collect transaction. Upon completion of a Collect, the IVR preferably sends a message back to the Main Script Engine.

15 The Transfer Call message function **148** is preferably used to transfer the caller to another telephone number. Typically, the transfer is to a customer service representative. The preferred types of transfers supported by the IVR Engine are blind, transfer connect, and CTI transfer.

In a blind transfer, the system preferably completes the call as soon as the
20 extension is dialed without waiting to determine if the third party is busy or answers. If the third party is busy or no one answers, the original caller normally typically hears a busy or ringing tone. It is typically not possible to reconnect the caller in these cases. Error conditions are usually not tracked even if they are returned to the call as there is no way to recover.

In a transfer connect, the system preferably waits for a connection to be established before completing a call. Any problems with the call like hardware/software/dial errors, timeout due to lack of call progress, illegal dial string or lack of dial tone at transfer are preferably relayed back to the calling application
5 for appropriate action.

A CTI (Computer Telephony Integration) transfer preferably allows transferring the call and simultaneously passing additional information about the call to an external system using CTI. The information may be passed in any appropriate way, such as in an Electronic Folder. The Electronic Folder preferably holds
10 information from the time a call comes in until the call is terminated. This information may be presented to the application and then to the agent. Data temporarily stored in the folder may include such information and the caller's account number, PIN number, address, social security number, and agent information.

15 A Transfer Call message may include a phrase tag(s) that plays a suitable message(s) to a caller before the transfer. An appropriate return value is preferably then sent back to the Main Script Engine. It might indicate whether the transfer was successful, depending upon the type of transfer.

The Message Coding function **150** is preferably sent from the Main Script
20 Engine to the IVR Engine to record speech from the caller. The message(s) is preferably preceded by a spoken phrase(s) to the caller to record at the beep. The IVR Engine then preferably plays a beep or other audible indicator to prompt the caller to start recording. The message length allowed, the talkfile, initial timeout, and completion timeout values may all be picked up from initial configuration, but

may be optionally set in the message. Again, the phrase number for each recording may be the next available number from the talkfile or sent as part of the message. Message coding information, including phrase number, machine name, and talkfile are then preferably sent back to the Main Script Engine if successful. A return value
5 may also be sent to indicate whether the recording was successful.

Coded messages may be retrieved (e.g., for transcription of message of the day) as a special Announce message from the Main Script Engine to the IVR Engine. The Announce message preferably includes the machine name, talkfile, and phrase tag(s)/phrase number(s).

10 Message coding is preferably of two different types: messages recorded by the caller (such as fulfillment information) and administrative messages (of the “message of the day” kind). Customer-recorded messages may remain on and be retrieved from the machine where they were recorded. Thus, the machine name may have to be passed to the Main components along with the rest of the message
15 information. The machine name would then preferably be returned along with the other phrase details to the IVR engine for transcription. Administrative messages may have to be distributed to all Voice Response machines for the project and be available for announcement.

The Disconnect function **144** is preferably used to direct the IVR Engine to
20 disconnect the system from the caller. The IVR Engine may then be freed up to perform housekeeping or other functions before terminating itself. An appropriate phrase(s) may be passed with the Disconnect message to be played back to the caller before hanging up.

The Error Condition function preferably sends any problem in the Main Script Engine back to the IVR Engine. Typically, this would be a condition that triggers an alarm from the Main System to any monitoring system used. The message preferably includes information about the seriousness of the error condition (major, minor, or informational), mutually designated message ids and possibly a phrase tag(s) (or number(s) designating a phrase) that may have to be played back to the caller.

The IVR Engine, on receiving the call from the switch, preferably sends the Initialize message to the Main Script Engine. This is the preferred point of transferring control of the call flow to the Script Engine. The routing of the message to the correct instance of the Script Engine is preferably controlled by the DNIS/VDN information of the incoming call, which is passed to the IVR DIP. The IVR DIP may use lookup configuration tables to route the messages appropriately. A return value is then preferably sent back to the IVR Engine to indicate whether the connection was successful.

The Hang-Up Event function **154** preferably sends a message from the IVR Engine to the Main Script Engine to notify the main system that the customer has hung up on the call. This enables both the engines to perform housekeeping functions and terminate the call and call flow respectively.

The Alarm function **156** preferably sends an error condition in the IVR Engine back to the Main Script Engine. Typically, this would be a condition that triggers an alarm from the IVR to any monitoring system used. The message preferably includes information about the seriousness of the error condition, mutually

designated message ids, and possibly a message string with additional useful information.

The Heartbeat function preferably sends a message from the IVR DIP with information about the 'health' of the IVR system at pre-set time intervals to the Main Script Engine. A reply with an appropriate return value at a pre-determined time interval is then preferably expected back to determine if the Script Engine is working normally.

A preferred layout exists for messages passed between the IVR Engine and the Main Script Engine. This preferred message structure provides flexibility in constructing and interpreting messages at either end of the system. Each message preferably includes a series of sections, some of which are optional. Each section preferably has a label that identifies the start of the section. While the size and layout of some section(s) may be fixed, other sections may store variable length data. The message structure may assume that all data, including the cache, consists of ASCII characters. The preferred message sections include the Header, the Data, the Cache, and the End of Message sections.

The Header section preferably contains the identity of the project the call belongs to, the type of message, and information for interpreting other sections of the message. The header fields are preferably fixed in length and extend to a length of about 35 bytes. The fields preferably post-fill with spaces if the size of the data is less than the field length. Preferred fields include HDR_LABEL, PROJECT_ID, MESSAGE_TYPE, FIELD_DELIMETER, and RETURN_CODE. The HDR_LABEL field preferably indicates the beginning of the header section and preferably has a constant value, such as "HDR". The PROJECT_ID field preferably

has the value that is used in the system, such as in the configuration file, to uniquely identify the project. The preferred valid types for the MESSAGE_TYPE field are Star Script, Collect, Message Coding, Transfer, Disconnect, Error, Alarm, Hang-Up, and No Action Type. The FIELD_DELIMITER may contain any character that does not occur in any of the other fields in the message, especially in the data section. The RETURN_CODE field may mainly be used by the IVR Engine to indicate success or failure in performing the message instruction sent from the Main Script Engine.

The Data section preferably contains the actual data component of the message. For messages sent from the Main Script Engine, this section preferably contains the next set of instructions to be performed in the IVR Engine. Messages from the IVR Engine preferably include data collected as a response to these instructions or any additional information sent to the Main Script Engine. The fields in this section are preferably DATA_LABEL, FIELD_DELIMITER, DATA_MSG_FUNCTION, and DATA_MSG_PARAMS. The size of this section is preferably variable, depending on the size of data in the DATA_MSG_PARAMS.

The DATA_LABEL field preferably indicates the start of the Data section. For messages from the Main Script Engine, it preferably has an appropriate value, such as "DIN". Outgoing messages from the IVR Engine have a corresponding value, such as "DOT". For messages from the Main Script Engine, this section may be mandatory as it carries the next set of instructions to be executed by the IVR Engine. It is optional for messages from the IVR Engine, and may be present only when it collects data, usually from the caller such as in the DATA_MSG_PARAMS field, that has to be passed on to the Script Engine.

This section preferably includes three functions: Options, Announce, and the function specified in the MESSAGE_TYPE field in the Header section. The Options and Announce functions may be available only to messages from the Main Script Engine. The MESSAGE_TYPE field should preferably be included for all message functions that have valid DATA_MSG_PARAMS fields. The number of items in the Options and Announce lists may be set to zero. Message functions that do not require any data to be passed to them may not have the MESSAGE_TYPE field in this section. For the same message type, the data parameters under DATA_MSG_PARAMS may be different, depending on whether the data section is “DIN” or “DOT”. If the section has an Options function, the sub-section with its parameters is preferably the first one. Similarly, the subsection with the MESSAGE_TYPE function, if present, is preferably the last one in the set of subsections. This implies that the Announce subsection, if it exists, preferably precedes the MESSAGE_TYPE subsection but follows the Options subsection.

The Cache section preferably has data that may be required by the Main Script Engine for successfully navigating the script flow. This may include ‘context’ information for establishing the current position of the script flow. This information is preferably not used at all by the IVR Engine but simply collected and sent back to the Main Script Engine with the response to the message. The pre-defined fields in this section are preferably separated from each other using the FIELD_DELIMITER value specified in the Header section. The preferred fields in this section include CACHE_LABEL, FIELD_DELIMITER, CACHE_DATA_SIZE, AND CACHE_DATA. The size of the section may be variable, preferably depending on the size of data in the CACHE_DATA field. The CACHE_LABEL field preferably indicates the start of

the Cache section and has an appropriate value such as "CAC". This section may be optional. The Main Script Engine may determine whether or not it needs a placeholder on the message to store any data it needs. The IVR engine may copy this section from each incoming message without changes to any messages it sends out before the next incoming message. The size of the CACHE_DATA field preferably matches the value in the CACHE_DATA_SIZE field. It may be used to provide independent confirmation of the receipt of the complete message.

The END_OF_MESSAGE section preferably marks the end of the message. It may be used to verify that the complete message has been received at either end of the system. The only field preferred to be in this section is EOM_LABEL. The EOM_LABEL field preferably has an appropriate consistent value, such as "END".

The Announce and Options Message Functions may be combined for use with existing message types or used by themselves. To avoid ambiguity, the No Action message type may be available for use with the Announce and Options message functions to indicate that no further action, other than the actual announce and/or options function execution, is necessary by the IVR Engine.

The preferred embodiments herein disclosed are not intended to be exhaustive or to unnecessarily limit the scope of the invention. The preferred embodiments were chosen and described in order to explain the principles of the present invention so that others skilled in the art may practice the invention. Having shown and described preferred embodiments of the present invention, those skilled in the art will realize that many variations and modifications may be made to affect the described invention. Many of those variations and modifications will provide the

same result and fall within the spirit of the claimed invention. It is the intention, therefore, to limit the invention only as indicated by the scope of the claims.

WHAT IS CLAIMED IS:

1. A method for processing telephone calls using IVR, said method comprising the steps of:
 - (a) automatically answering a call from an individual and redirecting said call to
5 an IVR Engine;
 - (b) sending a signal from said IVR Engine to a Script Engine, whereby said Script Engine may run an appropriate script and send an instruction back to said IVR Engine;
 - (c) passing said instruction from said IVR Engine to said individual;
 - 10 (d) collecting input from said individual given in response to said instruction; and
 - (e) terminating said call.
2. A method according to claim 1 additionally comprising the step of sending an appropriate message to said individual before terminating said call.
3. A method according to claim 1 additionally comprising the step of repeating steps
15 (b) through (d) until all data has been received.
4. A method according to claim 1 additionally comprising the step of applying business rules and logic to said input on said Script Engine.
5. A method according to claim 1 additionally comprising the step of utilizing project configuration information to establish a connection between said IVR Engine and
20 an appropriate said Script Engine.
6. A method according to claim 1 additionally comprising the step of automatically restarting upon encountering otherwise unrecoverable events.
7. A method according to claim 1 additionally comprising the step of warehousing said input.

8. A method according to claim 1 additionally comprising the step of executing appropriate APIs for said call.

9. A method according to claim 1 additionally comprising the step of validating said input on said Script Engine.

5 10. A method according to claim 1 additionally comprising the step of translating any incoming and outgoing information between said individual and said IVR Engine.

11. A method according to claim 1 additionally comprising the step of translating between said IVR Engine and said Script Engine.

10 12. A method according to claim 1 additionally comprising the step of setting up application-specific speech and configuration files for said IVR Engine.

13. A method according to claim 1 additionally comprising the step of generating a configuration file for said IVR Engine.

15 14. A method according to claim 1 additionally comprising the step of generating an electronic folder for each said call, said electronic folder adapted to house any information pertinent to said call.

15. A system for processing a telephone call from an individual using IVR, said system comprising:

(a) a switch, said switch adapted to automatically answer and redirect said telephone call;

20 (b) an IVR Engine, said IVR Engine adapted to accept said call redirected by said switch, said IVR Engine adapted to send outgoing information to and receive incoming information from said individual; and

(c) a Main Script Engine, said Main Script Engine adapted to receive an instruction from said IVR Engine, execute a script, and return an instruction to said IVR Engine.

16.A system according to claim 15 additionally comprising a data storage device for housing said incoming information received from said individual.

17.A system according to claim 15 additionally comprising a Computer Telephony Interface adapted to connect and provide a means of communication for said IVR Engine and said call.

18.A system according to claim 15 additionally comprising a main system containing said Script Engine.

19.A system according to claim 18 wherein said main system is adapted to warehouse said incoming information, apply business rules and logic to said information, and return data and analysis of said information.

20.A system according to claim 15 additionally comprising an Applications Program Interface.

21.A system according to claim 20 wherein said Applications Program Interface comprises functions selected from the group consisting of Announce functions, Disconnect functions, Collect functions, Transfer Call functions, Message Coding functions, Speech Recognition functions, Hang-Up Event functions, Alarms functions, Temporary IVR Transaction Suspension functions, Call Bridging functions, Auto-Faxing functions, Multi-lingual capability functions, and Application Switching functions.

22.A system according to claim 15 wherein said Script Engine is adapted to execute data validation.

23.A system according to claim 15 additionally comprising a socket interface between said IVR Engine and said Script Engine.

24.A system according to claim 23 wherein said socket interface comprises a TCP-IP socket.


5 25.A system according to claim 15 additionally comprising a Message Translator adapted to interpret said incoming and outgoing information.


26.A system according to claim 15 additionally comprising a Script Message Emulator, said Script Message Emulator adapted to simulate said Script Engine and interface with said IVR Engine.


10 27.A system according to claim 15 additionally comprising a DIP adapted to interface between said IVR Engine and said Script Engine.

ABSTRACT OF THE INVENTION

The present invention relates generally to voice response systems. Specifically, this invention relates to an interactive voice response client using script engines to control various voice processing systems. In a preferred embodiment, a customer dials a designated phone number and is connected to a main switch of the system. The switch sends a message pertaining to the call to a Computer Telephony Integration system, which in turn sends a signal to an IVR Engine. The IVR Engine is adapted to send and receive data from the caller. The IVR Engine also interacts with a Script Engine that is adapted to run any appropriate scripts, such as a script to apply business rules or logic. The Script Engine sends instructions to the IVR Engine, which are then passed on to the caller. Responses from the caller to the IVR may then be passed back to the Main Script Engine. This process repeats itself until all data is gathered or the call is terminated.

**FIG. 1**

**FIG. 2**

**FIG. 3**

Please type a plus sign (+) inside this box --> +

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	CON1246-076		
	First Named Inventor	Pirasteh et al.		
	<i>COMPLETE IF KNOWN</i>			
	Application Number	/		
	Filing Date	June 14, 2000		
	Group Art Unit			
<input type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input checked="" type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Examiner Name	

As a below named inventor, I hereby declare that:				
My residence, post office address, and citizenship are as stated below next to my name.				
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:				
<div style="border: 1px solid black; padding: 5px; margin: 5px auto; width: 80%;">METHOD AND SYSTEM FOR PROCESSING TELEPHONE CALLS BY IVR</div>				
the specification of which (Title of the Invention)				
<input type="checkbox"/> is attached hereto				
OR				
<input checked="" type="checkbox"/> was filed on (MM/DD/YYYY) 06/14/2000 as United States Application Number or PCT International				
Application Number and was amended on (MM/DD/YYYY) (if applicable)				
I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.				
I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.				
I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.				
Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?
			YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:				
<input type="checkbox"/> I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.				
Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.		

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION -- Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
I Rpt here

Name	Registration Number	Name	Registration Number
Jeffrey S. Standley	34,021		
Jeffrey C. Norris	42,039		
Cheryl S. Scotney	46,218	Carol G. Stovsky	42,171

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label ☒ Correspondence address below

Name	JEFFREY S. STANDLEY				
Address	Standley & Gilcrest LLP				
Address	495 Metro Place South, Suite 210				
City	Dublin,	State	Ohio	ZIP	43017
Country	USA	Telephone	614-792-5555	Fax	614-792-5536

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))		Family Name or Surname			
Hassan		Pirasteh			
Inventor's Signature				Date	
Residence: City	Jacksonville	State	Florida	Country	USA
Post Office Address	9313 Wesley Cove Court				
Post Office Address					
City	Jacksonville	State	Florida	ZIP	32257
				Country	USA

☒ Additional inventors are being named on the ¹ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (3-97)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet

Page 1 of 1

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

John

Garrow

Inventor's
Signature

Date

Residence: City

State

Country

Citizenship

Post Office Address

Post Office Address

City

State

ZIP

Country

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Shelly

Grossmith

Inventor's
Signature

Date

Residence: City

State

Country

Citizenship

Post Office Address

Post Office Address

City

State

ZIP

Country

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Khadim

Hussain

Inventor's
Signature

Date

Residence: City

State

Country

Citizenship

Post Office Address

Post Office Address

City

State

ZIP

Country

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.